

Red Oxide Silicone Coated Glass Fibre Tape



SRF Fire Sleeve tape is manufactured from 'E' glass fibre yarn, woven into a tape. Coated with high-grade silicone elastomer rubber.

What's it used for?

SFR Fire Sleeve tape is a very flexible tape designed to protect wires, cables, and hoses from high ambient temperatures.

It will offer continuous protection at an operating temperature of 250°C and can withstand a molten metal splash at 1200°C.

It is highly resistant to most oils, hydraulic fluids, fuels, acids and alkalis. The high grade rubber forms a protective SiO₂ layer when exposed to flame.

It provides personnel with protection against burns from hot boxes, steam lines etc. and helps to reduce energy loss by retaining heat within the pipework.

Quick Facts

Standard colour:	Red Oxide
Continuous operating temp:	250°C (482°F)
Molten splash resistance:	Outstanding
Flame resistance:	Very good
Abrasion resistance:	Very good
Flexibility:	Outstanding
Water and oil resistance:	Outstanding
Wall Thickness:	3-4mm
Average Dielectric Strength:	30Kv +

- ✓ Complies with EN 45545-2
- ✓ Tested to ISO 11925-2
- ✓ Meets requirement for IEC 60695-11-10
Classified as HB and V0
- ✓ Meets requirements for UL94 rating V0, V1, V2

An additional glass locked edge is best suited for ready cut custom sizes.

Standard format

Widths available::	25mm, 50mm, 75mm, 100mm, 125mm
Method of supply:	30mtr coils



US Mine Safety and Health Administration Approved

S Riley Fabrications

Unit 12 Habergham Mill, Coal Clough Lane, Burnley, Lancashire, BB11 5BS United Kingdom

www.srileyfabrications.co.uk

Info@srileyfabrications.co.uk

+44 1282 423336